

## NO - TOIL air filter oil

Store in a well-ventilated place, preferably whole.

Wear protective gloves and safety glasses when handling.

Mix well before use!!

Instructions for use:

1) if your filter is lubricated with mineral oil wash the filter first in solvent and then in detergent, 2) let the filter dry completely, 3) shake the container well before using the oil, 4) dip the filter in NO-TOIL oil 5) squeeze the filter well to get rid of excess oil, 6) let the filter dry for 15 minutes to allow the alcohol to evaporate and after this time you can install the filter on your motorcycle.

### WARNING:

Store out of reach of children. Highly flammable. Irritating to skin.

Harmful: risk of serious damage to health by prolonged inhalation. Toxic to aquatic organisms, may have long-term adverse effects on the aquatic environment. May damage internal organs if swallowed. Vapours may cause drowsiness and dizziness. Keep container in a well-ventilated place. Store away from food, drink and pet food. Do not pour oil down the drain, dispose of used material and can at a special collection point. Wear special protective clothing and gloves when handling. If ingestion occurs, seek medical attention immediately. If contact with eyes or skin occurs, rinse immediately with a stream of cold water and seek medical attention.

Dispose of the product environmentally after use.

Made in the USA

MEFO SPORT CENTRUM s.r.o., Jinín 60, Strakonice 38601, [www.mefo.cz](http://www.mefo.cz)